



MATERIAL SAFETY DATA SHEET

SECTION I – CHEMICAL PRODUCT AND COMPANY INFORMATION

This Material Safety Data Sheet covers the following products manufactured by Tower Industries.

MANUFACTURERS: Meridian Solid Surface
Tower Industries
2101 Ninth Street S.W.
Massillon, OH 44647
(330) 837-2216

EMERGENCY TELEPHONE NUMBER: (330) 837-2216

TELEPHONE NUMBER FOR INFORMATION: (330) 837-2216

DATE PREPARED: October 3, 2008
Werstler,

PREPARED BY: Todd
President

SECTION II – Hazardous Ingredients/Identify Information

<u>Hazardous Component</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>%</u>
----------------------------	-----------------	------------------	----------

This product does not contain regulated levels of NTP, IARC, or OSHA listed carcinogens.

This product produces nuisance particulate as identified by ACHIH and OSHA upon sawing, machining, sanding or routing.

TWA 15mg/m3 (Total Dust)	TWA 10mg/m3 (Inhalable Particulate)
STEL (none)	STEL (none)
TWA 5mg/m3 (Respirable Particulate)	TWA 10mg/m3 (Respirable Particulate)
STEL (none)	STEL (none)

SECTION III – Physical/Chemical Characteristics

BOILING POINT:	N/A	SPECIFIC GRAVITY:	1.75
VAPOR PRESSURE:	N/A	MELTING POINT:	N/A
VAPOR DENSITY:	N/A	EVAPORATION RATE:	N/A
SOLUBILITY IN WATER:	Insoluble in water.		
APPEARANCE AND ODOR:	Solid, no odor.		

SECTION IV – Fire and Explosion Data

FLASH POINT: N/A

FLAMMABLE LIMITS:

LEL N/A
UEL N/A

EXTINGUISHING MEDIA: This material is considered a “Class A” type combustible material. Use water spray, carbon dioxide, or dry chemical foam to extinguish flames. Use water to keep cool and prevent rekindling. Wear self-contained positive pressure breathing apparatus and full fire fighting protective clothing.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Machining, sawing, routing, and/or sanding of this product a Class ST-1 dust. Safety precautions (and proper ventilation) as recommended by NFPA-68 for Class ST-1 dusts should be followed to prevent this or any Class ST-1 dust from presenting an explosion hazard.

SECTION V – Reactivity Data

STABILITY: STABLE X UNSTABLE
CONDITIONS TO AVOID: None known.

INCOMPATIBILITY (MATERIALS TO AVOID): Organic solvents, strong acids or alkaline solutions will destroy the luster or surface appearance.

HAZARDOUS DECOMPOSITION BYPRODUCTS: May produce Carbon Monoxide, Carbon Dioxide, smoke, and/or oxides of nitrogen.

HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR X
CONDITIONS TO AVOID: None known.

SECTION VI – Health Hazard Data

ROUTES OF ENTRY: The potential routes of entry are inhalation, ingestion, skin contact, and eye contact.

Inhalation: Nuisance Dust – Overexposure to dust may cause irritation of the respiratory tract. Should this happen, remove affected individual to fresh air. If symptoms persist, consult a physician.

Ingestion: Nuisance Dust – may cause direct tissue irritation but is not expected to cause a significant toxic response. Call physician. DO NOT induce vomiting.

Skin & Eye: Nuisance Dust – May cause irritation. Wash skin with soap and water, flush eyes with water for at least 15 minutes. Contact physician if irritation persists.

HEALTH HAZARDS (Acute and Chronic): This product is not hazardous in normal use. During fabrication operations (such as sawing, drilling, routing and sanding) dust, consisting of cured resin are generated at the cutting face.

SECTION VII – Precautions for Safe Handling and Use

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: This material is non-hazardous. Sweep up/pick up scrap material and place in disposal containers.

WASTE DISPOSAL METHOD: Scrap material and dust may be disposed according to applicable Federal, State, and local regulations. This product is non-hazardous under RCRA.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Safety glasses, gloves, and safety shoes should be worn when handling or machining material to prevent cuts and abrasions.

OTHER PRECAUTIONS: Maintain adequate ventilation to maintain airborne concentrations of dust below the exposure limits.

SECTION VIII – Control Measures

EXPOSURE CONTROL METHODS:

Provide sufficient ventilation and dust pick-up at saw, sander, drill or router to keep dust level below 10mg/cubic meter TWA or provide and make mandatory the wearing of NIOSH approved dust respirators.

SECTION IX – OTHER REGULATORY INFORMATION

SHIPPING DESCRIPTION: Not regulated by the Department of Transportation (D.O.T.)

HAZARDOUS MATERIAL CLASS: Non-hazardous

LABELLING: None

REVISION HISTORY:

Date of Issue: 10/3/08

Supersedes all previous issues.

The information and statements herein are believed to be reliable but are not to be construed as a warranty or representation for which Tower Industries assumes legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. TOWER INDUSTRIES MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HEREIN. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY EXCLUDED.